



INSTRUCTIONS

TANK DRY™ TOOL (“TDT”)



CONGRATULATIONS ON CHOOSING THE AMAZING WATER HOG® TANK DRY™ TOOL TO REMOVE WATER FROM FUEL!

- **BEFORE USING WATER HOG® PRODUCTS, CAREFULLY READ ALL INSTRUCTIONS & VIEW INSTRUCTION/INFO VIDEOS AT WWW.MYTANKDRY.COM & WWW.MYWATERHOG.COM**
- **IT IS ESSENTIAL TANK DRY™ TOOL MUST BE ALLOWED TO FALL AS QUICKLY AS POSSIBLE TO THE TANK BOTTOM. BE SURE TO SECURE THE CONTROL LOOP ON THE END OF THE ROPE AROUND YOUR WRIST TO AVOID IT FALLING INTO THE TANK. ONLY WATER HOG® TANK DRY™ TOOL AND REFILLS ARE INTENDED FOR DIRECT USE IN FUEL! TANK DRY™ TOOL IS NEVER TO BE INSERTED INTO THE FUEL FILL PIPE!!**
- **Keep WATER HOG® dry until use. WATER HOG® activates rapidly upon contact with water. Depending on temperature, you should get full water absorption in 5 to 10 minutes.**
- **To deploy, connect WATER HOG® TANK DRY™ REFILL to the cable in the TANK DRY™ TOOL by hooking the included Snap Hook through the grommet at one end of the refill, then gently pull it up into the rigid sleeve until it stops at the top end of the sleeve. Carefully lower it into the fuel storage tank. If you encounter ANY obstructions, stop and remove this device immediately! Seek qualified assistance. Always remove WATER HOG® slowly and carefully.**
- **Easy disposal: Simply let air dry, or dry more rapidly by cutting open and emptying gel contents into a pan or tub. Drying can be accelerated substantially by sprinkling table salt on the wet gel content - in minutes it becomes a watery liquid. Once dehydrated, a small amount of residue will remain for disposal. Always comply with all local, state & federal disposal regulations.**
- **Only qualified personnel very familiar with fuel tanks should use TANK DRY™ TOOL. If any concerns, contact our help line before proceeding. In each case you will be given general information and referred to a qualified party. Always wear proper safety protection around fuel. We accept no liability or responsibility for damage to equipment, sumps, UDC's, tanks, components, fuel, or personal injury or misuse of WATER HOG® in any way.**
- **PLEASE ENSURE THAT SCREWS AND CORD CONNECTIONS REMAIN SECURE BEFORE EACH USE.**

PLEASE NOTE: SPECIFIC WATER HOG® MODELS ARE FOR SPECIFIC JOBS. Please use the correct model for the job. WATER HOG® products are not intended to absorb fuel or any hydrocarbon product. We supply special mats to absorb fuel-call for info. Use HI-STANDARD 2 foot or 4 foot WATER HOG®s for removal of water & sheen from SUMPS & UNDER-DISPENSER CONTAINERS. Use only TANK DRY® TOOL FOR FUEL TANKS. Use WATER HOG® “I.S.D.” for INTERSTITIAL SPACE applications in steel tanks with unobstructed vertical interstitial 2 inch I. D. or more access Riser. Use WATER HOG® SPILL BUCKET WIZARD™ for Spill Buckets. Always avoid jerking/tugging when lifting/removing all WATER HOG® models. Use slow steady motions in a professional workmanlike manner. Complex tank plumbing & other impediments including sharp edges may cause snags that can result in contents being released into fuel, or difficult retrieval. Avoid rough handling & bending after water contact. Always wear proper safety protection around fuel. We accept no liability or responsibility for damage to equipment, sumps, UDC's, tanks, components, fuel, personal injury or misuse of WATER HOG® in any way including alterations of our products or use of non-WATER HOG® refills in our products. USA & INTERNATIONAL PATENTS PENDING.

Questions? Call 877-500-7745 ext. 700. For more, please go to



MYWATERHOG.COM

By MONARCH GREEN, INC.